


















































Bluetooth Equipment

Model	Part Number	Price	Device Type	Interface	Standards Compliance	Operating System	Dimensions	Weight	Warranty	Features	Image
3Com											
Wireless Bluetooth PC Card	3CRWB6096B	\$99.95	Adapter	Type II PCMCIA Card	Dial-up networking profile, Standards-based software architecture, Bluetooth 1.1, Service Discovery Protocol, Serial Profile, Object Push profile	Windows 98SE, 2000, ME, XP, Pocket PC 2000 and Pocket PC 2002			3 years		
Wireless Bluetooth Adapter	3CREB96B	\$89.95	Adapter	USB 1.1	Dial-up networking profile, Standards-based software architecture, Bluetooth 1.1, Service Discovery Protocol, Serial Profile, Object Push profile	Windows 98SE, 2000, ME, XP, Pocket PC 2000 and Pocket PC 2002			3 years		
Anycam											
Blue PC Card (CF + PC Card Adapter) CF-300	CC3042	\$99.99	Adapter	CF Card with PCMCIA Adapter	Bluetooth 1.1, CF Card Type 1, PC Card Type 2, supported profiles: GAP, SDP, SPP, DUN, LAP, FAX, ObexFT, ObjectPush, HCRP	CE.net version 4.1/4.2 with Strong Arm, Xscale, Mips R4000 and SH3, Windows mobile/Pocket PC 2003	47x43x3mm (CF Card), 97x53x3mm (with PC Card adapter)	18 grams CF Card only, 37 grams including PC Card adapter	2 years	Max speed up to 1Mbps gross, range up to 10 meters, secured with password and PIN code, data transfer coded with up to 128-bit encryption, integrated antenna, green status LED, orange traffic LED	
Blue Compact Flash Card CF-3000	CC3044	\$99.99	Adapter	CF Card	Bluetooth 1.1, CF Card Type 1, PC Card Type 2, supported profiles: GAP, SDP, SPP, DUN, LAP, FAX, ObexFT, ObjectPush, HCRP	CE.net version 4.1/4.2 with Strong Arm, Xscale, Mips R4000 and SH3, Windows mobile/Pocket PC 2003	47x43x3mm	18 grams	2 years	Max speed up to 1Mbps gross, range up to 10 meters, secured with password and PIN code, data transfer coded with up to 128-bit encryption, integrated antenna, green status LED, orange traffic LED	
Blue USB Printer Module PM-300		\$99.99	Print Server	USB 1.1	Bluetooth 1.1, GAP, SDP, SPP, HCRP		66x57x29mm	40 grams	2 years	Max speed to 1Mbps gross, range up to 100 meters, secure access and dedicated communication with password and device specific PIN-code, 128-bit encryption conforming to Bluetooth specification, integrated antenna, power and activity LED indicators	
Blue Printer Adapter PM-400		Not Available	Print Server	USB 1.1, Parallel Port	Bluetooth 1.1, GAP, SDP, SPP, HCRP		3.14x2.36x0.826"	61 grams	2 years	Max speed up to 1Mbps gross, CSR BC02 chip set, range up to 100 meters, secure access and dedicated communication with password and device specific PIN-code, 128-bit encryption conforming to the Bluetooth specification, changeable device name, integrated antenna, Power, Bluetooth Connection and data transfer LED indicators	
Blue Printer Card CF-300	CC3029	\$99.99	Print Server for HP DeskJet 450	CF Card Type I	Bluetooth 1.1, SPP, HCRP, Object Push, BPP (basic printing)	HP DeskJet 450	47x43x3mm	18 grams	2 years	Max speed 1Mbps gross, range up to 10 meters, secured with password and PIN code, data transfer coded with 128-bit encryption according to Bluetooth specification, integrated antenna, green status LED, orange traffic LED	
Blue AP-2002 Access Point		\$169.99	Access Point	10/100 Ethernet	Bluetooth 1.1		155x120x20mm	200 grams	2 years	Range up to 100 meters, 7 simultaneous users supported, point-to-multipoint and master/slave support, upper layer protocols HCI and above (L2CAP, SDP, RFCOMM), HCI Transport UART (RS232), data packets DM1/DH1, DM3/DH3, DM5/DH5, integrated antenna, SNMP version 1, 2 and 3 management, power, network activity, status LED indicators, flash upgradeable for firmware updates over the Web	
Blue USB-100 USB Adapter		Not Available	Adapter	USB 1.1	Bluetooth 1.1, GAP, SDP, SPP, DUN, LAP, FAX, ObexFT, ObjectPush, HCRP, PAN, Headset, Sync, HID profiles		10x57x44mm	9 grams	2 years	Max speed 1Mbps gross, range up to 30 meters, secured with password and PIN code, data transfer coded with up to 128-bit encryption according to Bluetooth specifications, integrated antenna, blue status LED	
Blue USB Adapter USB-120		\$39.99	Adapter	USB 1.1	Bluetooth 1.1 (1.2 ready), GAP, SDP, SPP, DUN, LAP, FAX, ObexFT, ObjectPush, HCRP, PAN, Headset, Sync, HID profiles	Windows 98SE, ME, 2000, XP, Linux, Macintosh OS X 10.3	10x52x17mm	11 grams	2 years	Max speed 1Mbps gross, Silicon Wave chipset, range up to 100 feet, secured with password and PIN code, data transfer coded with up to 128-bit encryption according to Bluetooth specifications, integrated antenna, status LED	
Blue USB Adapter USB-240		\$49.99	Adapter	USB 1.1	Bluetooth 1.1 (1.2 ready), GAP, SDP, SPP, DUN, LAP, FAX, ObexFT, ObjectPush, HCRP, PAN, Headset, Sync, HID profiles	Windows 98SE, ME, 2000, XP, Linux, Macintosh OS X 10.3	93.5x26.7x13mm	14 grams	2 years	Max speed up to 1Mbps gross, Silicon Wave chipset, range up to 328 feet, secure access and dedicated communication with password and device specific PIN code, 128-bit encryption conforming to the Bluetooth specification, integrated antenna, status LED	
Blue TV Adapter TV-BT04		Not Available	Adapter	21 pin male SCART connector for video and stereo sound, RCA mini jack for video and mono sound	Bluetooth 1.1, PAL TV (NTSC coming), JPEG, OBEX (Object Push) and FTP (File Transfer) profiles	Sony Ericsson T39M, T68, T68, Z600, P800, P900, Nokia 3650, 6310, 6310i, 8910, 8600, Siemens S55, S11 phones (more information available at Anycam web site)	60x78x18mm	53 grams	2 years	Range up to 10 meters, MP3 audio format, 128Kbps bit rate with 44kHz, 16-bit stereo sampling rate, display of ID-3 tag information, AIR files up to maximum allowed file size of 30Kbyte, VGA resolution (640x480), SVGA (600x800) max	
Asante											
FriendlyNet FBT100	99-00630-07	\$29.95	Adapter	USB 1.1	Bluetooth v 1.1, File transfer, Dial-up networking information exchange, fax and network access	Windows 98SE, ME, XP, Pocket PC 2000, Pocket PC 2002	0.38x0.75x1.83"	0.18 lbs.	2 years	723 Kbps speed, range 33 feet	
Axis Communications											
9010 Bluetooth Access Point	0128-004-04	\$349.00	Access Point	10/100 Ethernet	Bluetooth v 1.0B	Windows	7x2x5.6"	0.7 lbs	2 years	Embedded Linux operating system, built-in web server, PAP, RADIUS authentication, DHCP support, link activity, power status LED indicators	

Bluetooth Equipment

8500+ Mobile Network Print Server		\$430.95	Print Server	10/100 Ethernet, two 25-pin DSUB parallel ports	Bluetooth Axis Print Profile, Object Push Profile	Windows NT version 3.5 and above, Windows for Workgroups 95, 98, ME, 2000, XP, Novell NetWare 3.11, 3.12, 4.10, 4.15 5 and above, Microsoft LAN Manager 2.0c and above, running under OS/2 ver. 1.3 and above, IBM LAN Server 1.3 and above running under OS/2 ver 1.3 and above including OS/2 Warp, OS/2 Warp Connect, LANtastic 7.0, BSD 4.2, 4.3, 4.4, Sun OS4, DEC Ultrix, System V R3, R4, AT&T Interactive, SCO, SunOS5, HP-UX, Silicon Graphics IRIX, DEC Alpha OSF/1, IBM AIX, BULL (BOS, AIX), Linux, IBM MVS, VM, VSE OS/400, DEC VMS, Apple EtherTalk	1.1x6.7x5.5"	0.57 lbs.	2 years	NetWare encrypted passwords, Packet Signature Level 1, 2, 3, UNIX/Linux root password, user access list and printer access, SNMP MIB II compliant, print server/job/printer status presentation and management via NWAdmin/PCONSOLE, AXIS ThinWizard for monitoring, configuration and firmware upgrades, programmable printer ports to perform auto aSCII to PostScript conversion, string before and after job, string substitution, alternative output and character set conversion, Power and network LEDs, test button for information printouts	
8810 - Bluetooth Print Plug		Not Available	Print Server	Parallel Port, Centronics Connector	v 1.1 certified, Axis Print Profile, Hardcopy Cable Replacement Profile, Serial Port Profile, Object Push Profile	Bluetooth enabled systems and devices	7.87x2.44x2.83"	0.11 lbs.	2 years	Power supplied over parallel port, 460 Kbps performance over Bluetooth baseband link, firmware upgradable, 32-bit 100MHz RISC Controller, 512KB Flash Memory, 2MB RAM, Power and Network LED indicator, test button for information printouts	
Belkin											
Bluetooth PDA and PC Adapter Combo Card	F8T006-PC	\$109.99	Adapter	CompactFlash Type 1, PCMCIA	Bluetooth v 1.1	Windows 98SE, ME, 2000, XP, Server 2003, Pocket PC 2002 and 2003	52x43x5mm		Lifetime Limited	128-bit encryption and authentication	
Bluetooth USB Adapter	F8T001	\$69.99	Adapter	USB 1.1	Bluetooth v1.1, Human Interface Device	Windows 98SE, ME, 2000, XP, Server 2003, Macintosh OS X			Lifetime Limited	128-bit encryption and authentication	
Bluetooth USB Adapter	F8T003	\$59.99	Adapter	USB 1.1	Bluetooth v1.1, Service Discovery, File Transfer, LAN Access, Serial Port, DUN, Generic Object Exchange, Business Card, Push, Pull & Exchange, Fax, Synchronization	Windows 98SE, ME, 2000, XP, Macintosh OS X v 10.2 and higher	57x24x10mm	0.3 oz.	Lifetime Limited	LED indicator - power on/data traffic, 128-bit encryption and authentication	
Bluetooth Access Point with USB Print Server	F8T030	\$199.99	Access Point and Print Server	Two USB 1.1, 10/100 Ethernet	Bluetooth v1.1, Generic Access, Service Discovery, Serial Port, LAN Access, PAN Profile	Windows 98SE, ME, 2000, XP, Pocket PC 2000, Pocket PC 2002, Palm OS			Lifetime Limited	Print Server supporting line printout protocol, embedded web server with SSL, firewall, 128-bit encryption and authentication, DHCP support, NAT support	
Bluetooth Wireless USB Printer Adapter	F8T031	\$149.99	Print Server	USB 1.1	Bluetooth v1.1, Hardcopy Cable Replacement and Serial Port Profiles	Windows 98SE, ME, 2000, XP, PocketPC 2002, 2003, Palm OS			Lifetime Limited	Plug and Play, 100m range	
Digi											
Wavespeed/5 Class 1	301-1121-01	\$225.96	Adapter	Serial EIA-232 DB-9 female	Bluetooth 1.1	Windows 95, 98, 98SE, ME, 2000, XP, NT, NT Embedded	4.03x2.16x1.36"	2.0 oz.	5 years	100 meter range, software configurable as DTE or DCE device, baud rates of 300, 1200, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200 bps, 8 or 7 data bits, 1 or 2 stop bits parity - none, odd, even, flow control - none, software (user-specified XON/XOFF), hardware (RTS/CTS), LED for device, software and wireless link status, in range/out of range indicator	
Wavespeed/5 Class 2	301-1122-01	\$213.13	Adapter	Serial EIA-232 DB-9 female	Bluetooth 1.1	Windows 95, 98, 98SE, ME, 2000, XP, NT, NT Embedded	4.03x2.16x1.36"	2.0 oz.	5 years	10 meter range, software configurable as DTE or DCE device, baud rates of 300, 1200, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200 bps, 8 or 7 data bits, 1 or 2 stop bits parity - none, odd, even, flow control - none, software (user-specified XON/XOFF), hardware (RTS/CTS), LED for device, software and wireless link status, in range/out of range indicator	
D-Link											
PersonalAir Bluetooth USB Printer Adapter	DBT-320	\$75.00	Print Server	USB 1.1	Bluetooth v1.1, Hardcopy Cable Replacement Profile (HCRP), Serial Port Profile (SPP), Object Push Profile (OPP)	Bluetooth enabled PC, Mobile Phone or PDA	3.5x2x1.1"	0.22 lbs.	1 year	Dipole antenna, range up to 10m	
PersonalAir Wireless USB Bluetooth Adapter	DBT-120	\$45.00	Adapter	USB 1.1	Bluetooth v1.1	Windows 98SE, ME, 2000, XP, Macintosh OS X v 10.2	1.81x.73x0.37"	0.18 lbs.	1 year	Supports up to 7 slave devices, on-module RAM enables firmware updates from host computer, rates - 723Kbps asymmetrical, 433.9Kbps symmetrical, 128-bit encryption, on board antenna, range 33 feet (peer-to-peer)	
PersonalAir Stereo Adapter Kit	DSM-910BT	\$129.00	Stereo Adapter	3.5mm audio in and 3.5mm audio out jacks	Bluetooth v1.1		3.5x3.25x1.5"		1 year	Transfer rates 723Kbps asymmetrical, 433.9Kbps symmetrical, dipole antenna, 10 to 30m operating range, power and link LED indicators	
PersonalAir USB Stereo Adapter Kit	DSM-920BT	\$129.00	Stereo Adapter	MiniUSB, 3.5mm audio out jack	Bluetooth v1.1		3.5x3.25x1.5", 3x2x.75"		1 year	Transfer rates 723Kbps asymmetrical, 433.9Kbps symmetrical, dipole antenna, power and link LED indicators 10 to 30m operating range	
FIIC											
Bluetooth Dongle	BUS-001/BUS-002	Not Available	Adapter	USB 1.1	Bluetooth v1.1, Piconet support (1 to 7 slaves), GAP, SDAP, SP, DUN, FAX, LAN, OPP, FTP, OBEX, Synchronization profiles	Windows 98, ME, 2000, XP	97.3x30.5x12.5mm		1 year	Built-in authentication and encryption, mono audio in/out, 10 meter range, Silicon Wave chipset, 1Mbps symbol rate	
Bluetooth Module	BMS-001	Not Available	Internal Device Module	USB and UART	Bluetooth v 1.1,		33x20x3mm		1 year	Silicon Wave chipset, 79 channels, 10 meter range, 1Mbps symbol rate, voice interface with external CODEC, LC, LMP protocol stacks	
Hawking Technology											
Bluetooth USB Wireless Adapter	H-BT10U	\$49.00	Adapter	USB 1.1	Bluetooth v1.1	Windows 98, 2000, ME, XP	69.53x26.68x19mm		2 years	Supports 8 devices, range 33 feet, 723 Kbps	
Bluetooth USB Class 1 Wireless Adapter	HBTC1	\$39.00	Adapter	USB 1.1	Bluetooth v1.1	Windows 98, ME, 2000, XP, Macintosh OS X and above	69.53x26.68x9.19mm		2 years	Data rate to 723Kbps, data encryption to 128-bits, range of 100 meters, 8 devices point-to-multipoint, frequency-hopping spread spectrum RF topology, power LED indicator	
O Gear											

Bluetooth Equipment

Bluetooth CompactFlash Card	GBC201	\$69.95	Adapter	CompactFlash Type III	Bluetooth v 1.1, File Transfer, Dial-up Networking, Network Access-Client, Fax-Client, Object Push, Information Exchange Profiles	Pocket PC 2000, Pocket PC 2002	3.3x52x43mm		1 year	Pairing, encryption, authentication, power LED, user-friendly software, low power consumption, range 20m, 723/57.6Kbps	
Bluetooth USB Adapter - Class 2	GBU201	\$32.95	Adapter	USB 1.1	Bluetooth v 1.1, Generic Access, Serial Port, Dial-up Networking, Fax, LAN, Object Push, File Transfer, Synchronization Profiles	Windows 98SE, or later, Macintosh OS X	0.35x2.75x1.25"		1 year	pairing, encryption, authentication, 20m range, 723/57.5 Kbps	
Bluetooth to USB Adapter	GBU301	\$44.95	Adapter	USB 1.1	Bluetooth v1.1, Generic Access, Serial Port, Dial-up Networking, Fax, LAN, Object Push, File Transfer, Synchronization Profiles	Windows 98 or later, Macintosh OS X	0.35x2.75x1.25"		1 year	pairing, encryption, authentication, 20m range, 723/57.5 Kbps	
Bluetooth Networking Starter Kit	GBU302	\$79.99	Adapters	USB 1.1	Bluetooth v1.1, Generic Access, Serial Port, Dial-up Networking, Fax, LAN, Object Push, File Transfer, Synchronization Profiles	Windows 98 or later, Macintosh OS X	0.35x2.75x1.25"		1 year	2 USB adapters, pairing, encryption, authentication, 10m range, 723/57.6Kbps	
Bluetooth Combo Print Adapter	GBP301	\$103.95	Printer Adapter	IEEE 1284 Parallel, USB 1.1	Bluetooth v 1.1		0.8x2.1x3.25"	0.15 lbs.	1 year	723 Kbps, power, printer, Bluetooth LEDs	
USB Print Adapter with Bluetooth Wireless Technology	GBP201	\$69.99	Printer Adapter	USB 1.1	Bluetooth v 1.1, Pico-net and Scatter-net up to 7 devices, Bluetooth Class 2 device, HCRP (Hardcopy Cable Replacement Profile) and SPP (Serial Port Profile)		1.5x3x0.75"	0.15 lbs.	1 year	Range to 66 feet, 723Kbps data rate, power and link LED indicators	
Keyspan											
USB Bluetooth Adapter	BT-2A	\$30.95	Adapter	USB 1.1	Bluetooth v 1.1	Windows 98, 98SE, ME, 2000, XP, Macintosh OS X 10.1.4 or later		2 oz.	1 year	50 foot range	
Linksys											
Bluetooth USB Adapter	USBBT100	\$44.95	Adapter	USB 1.1	Bluetooth v1.1	Windows 98SE, 2000, ME, XP	2.95x0.12x0.33"	0.99 oz.	1 year	128-bit encryption and authentication, one LED, 721Kbps, supports up to 7 connections	
LiteOn											
USB Dongle	WB200	Not Available	Adapter	USB 1.1	Bluetooth v1.1, all defined profiles	Windows 98SE, 2000, ME, XP	60x20x14mm		1 year	723 Kbps, 16MB Flash Memory	
Micro Innovations											
Micro Bluetooth Dongles Share Kit	USB995BT	\$29.95	Adapter	USB 1.1	Bluetooth v 1.1	Windows 98SE, 2000, ME, XP	60x20x14mm		1 year	Two USB Bluetooth dongles and extension cables	
Micro Star											
BToes	MS-6970	Not Available	Adapter	USB 1.1	Bluetooth v 1.1	Windows 98, ME, 2000, XP			3 years	Range 10m, 723 Kbps, 79-channel system	
MS-6967	MS-6967	\$64.99	Adapter	USB 1.1	Bluetooth v 1.1	Windows 98, ME, 2000, XP			3 years	Range 10m, 723 Kbps, 79-channel system	
Orange Micro											
Blue2 Bluetooth USB Adapter	70BLU00001	\$39.00	Adapter	USB 1.1	Bluetooth v1.1, ClassII Bluetooth device, Bluetooth Serial Port, Dial-up Networking Fax, File Transfer, Headset, PIM Item Transfer, PIM Synchronization, Network Access, Audio Gateway Profiles	Windows 98SE, ME, 2000, XP, Macintosh OS X 10.2 or later	58.6x19.8x8.1mm		1 year	Pairing, encryption, authentication, 723Kbps, range - 30 feet, supports up to 7 simultaneous Bluetooth devices	
Blue2 Wireless Headset with Mic featuring JABRA FreeSpeak	70BLU00002	\$129.00	Headset and Adapter	USB 1.1	Bluetooth v1.1, ClassII Bluetooth device, Bluetooth Serial Port, Dial-up Networking Fax, File Transfer, Headset, PIM Item Transfer, PIM Synchronization, Network Access, Audio Gateway Profiles	Windows 98SE or later, Macintosh OS X	58.6x19.8x8.1mm		1 year	Pairing, encryption, authentication, 723Kbps, range - 30 feet, supports up to 7 simultaneous Bluetooth devices, includes JABRA FreeSpeak wireless headset, JABRA charging cradle, charging cradle clip for belt or purse, three JABRA MiniGels	
Pico Communications											
PicoBlue Internet Access Point	99-00729-01	\$379.00	Access Point	10/100 Ethernet, RS-232	Bluetooth v 1.1, LAN Access Profile (LA, selectable 1 to 7 users), Serial Port Profile (SPP), Generic Access Profile		8.125x6.125x1.5"	482 grams	1 year	723.2/57.6 Kbps asymmetric up to 433.9 Kbps symmetric, 100 meter range, Security Mode 1 (non-secure, Security Mode 2 (service level enforced security), Security Mode 3 (link level enforced security), 128-bit link level authentication, 9-128-bit link level encryption, Bluetooth address-based filtering, non-discoverable mode, HTTP re-direct, configuration access over Bluetooth or Ethernet LAN, HTTP, TELNET command line interface, RS-232 command line interface, RADIUS and TACACS+ support, DHCP client and server, static IP addressing, firmware upgradeable via FTP client with safe-mode protection, NAT support, PPP server, PAP, CHAP MDS support, LED status indicators for power, status, Bluetooth and Ethernet link and activity	
Red-M											
Red-Access		\$349.00	Access Point	Two 10/100 Ethernet Ports	Bluetooth v1.1, Generic Access, Service Discovery, Dial-up Networking and LAN Access, PAN1 Profiles		43x125x140mm		1 year	Web-based management, 32 simultaneous users supported, 723.2/57.6Kbps, DHCP client, DHCP relay agent, PPP, PPPoE, NAT, HTTP support	
Star Tech											
USB to Bluetooth Wireless Adapter	USBBT100	\$52.99	Adapter	USB 1.1	Bluetooth v1.1	Windows 98SE, 2000, ME, XP			Lifetime Limited	721 Kbps, range 50 feet, supports up to 7 simultaneous Bluetooth devices, 128-bit encryption, activity LED indicator	
Targus											
USB Bluetooth Adapter (Class 2)	ACB10US	\$39.99	Adapter	USB 1.1	Bluetooth v1.1, DUN, LAN, FAX, FTP, HID, HP, HCRP, SPP, GAP, GCEP, SYNCH, PAN, OPP, SDAP profiles (uses WIDCOMM Software v1.4)	Windows 98SE, ME, 2000, XP, Macintosh OS X	2.22x0.79x0.43"	0.45 oz.	1 year	Internet bridge, data rate 723/57.6Kbps	

Bluetooth Equipment

Bluetooth Mini Mouse with Bluetooth Adapter	AMB01US	\$79.99	Adapter/Bluetooth Mouse Combination	USB 1.1	Bluetooth v1.1, DUN, LAN, FAX, FTP, HID, HP, HCRP, SPP, GAP, GOEP, SYNCH, PAN, OPP, SDAP profiles (uses WIDCOMM Software v1.4)	Windows 98SE, ME, 2000, XP	3.5x2.1x1.1"	2 oz.	1 year	Includes high resolution 800dpi optical mouse, on/off switch to conserve battery life, 2 AAA batteries included, carrying pouch, data rate 723/57.6Kbps	
TRENDnet											
Bluetooth USB Adapter	TBW-101UB	\$19.99	Adapter	USB 1.1	Bluetooth v1.1	Windows 98SE, 2000, ME, XP			1 year	128-bit encryption, power LED indicator, 723 Kbps, range 33 feet, supports up to 8 point-to-multi-point devices	
High-Power Wireless Bluetooth USB Adapter	TBW-102UB	\$28.50	Adapter	USB 1.1	Bluetooth 1.1	Windows 98SE, ME, 2000, XP	2.75x1x0.35"	0.35oz.	1 year	723 Kbps, 128-bit WEP encryption, range of 330 feet, 79 channels, supports up to 8 point-to-multi-point devices	
UMAX											
BT500+BT009X Bluetooth Mouse + Adapter Bundle		\$89.00	Bluetooth Mouse and Adapter Bundle	USB 1.1	Bluetooth v1.1 compliant, service discovery	Windows 98SE, ME, 2000, XP, Macintosh OS X 10.2.6 or later	85.2x50x32.6mm	64 grams	1 year	800dpi optical technology mouse, scroll wheel with LED indicator, power on/off switch, 10 meter coverage area, data transfer rate to 723Kbps	
Bluetooth USB Printer Adapter	BT210	\$109.00	Bluetooth Printer Adapter	USB 1.1	Bluetooth v1.1 compliant (HCRP, SPP)	Windows 98SE, ME, 2000, XP, PocketPC 2003, 2002, 2000	92x41.5x42mm	30 grams	1 year	100 meter coverage area, data rate to 723Kbps, extendable antenna, powerlink status LED	
Bluetooth Parallel Printer Adapter	BT200	\$89.00	Bluetooth Printer Adapter	Parallel Port	Bluetooth v1.1 compliant (SPP)	Windows 98SE, ME, 2000, XP, PocketPC 2003, 2002, 2000	78.6x32x20.6mm	52 grams	1 year	10 meter coverage area, 1Mbps data rate, power/data receiving status LED indicator	
Bluetooth USB Adapter	BT009X	\$36.00	Adapter	USB 1.1	Bluetooth v1.1 compliant, service discovery	Windows 98SE, ME, 2000, XP, Macintosh OS X 10.2.6 or later	75x24.5x10.4mm	10 grams	1 year	10 meter range, 1Mbps data transfer rate	
Bluetooth USB 2.0 Pen Drive 256MB	BT009M	\$179.00	Adapter, Flash Memory Drive Combo	USB 2.0	Bluetooth v1.1 compliant, service discovery	Windows 98SE, ME, 2000, XP, Macintosh OS X 10.2.6 or later	78.9x22.1x10.2mm	14 grams	1 year	Data rate to 1Mbps, 10 meter range, flash drive 9Mbps reading speed, 8Mbps writing speed, write protection switch, 1,000,000 erase cycles, data retention up to 10 years, bus powered	
Bluetooth USB 2.0 Pen Drive 128MB	BT009M	\$109.00	Adapter, Flash Memory Drive Combo	USB 2.0	Bluetooth v1.1 compliant, service discovery	Windows 98SE, ME, 2000, XP, Macintosh OS X 10.2.6 or later	78.9x22.1x10.2mm	14 grams	1 year	Data rate to 1Mbps, 10 meter range, flash drive 9Mbps reading speed, 8Mbps writing speed, write protection switch, 1,000,000 erase cycles, data retention up to 10 years, bus powered	
Zoom											
USB Adapter	4310	\$39.95	Adapter	USB 1.1	Bluetooth v1.1, General Access Profile (GAP), Service Discovery Application Profile (SDAP), Serial Port Profile (SPP), Dial-up Networking Profile (DUN), Fax Profile, Local Area Network Access Profile (LAP), Generic Object Exchange Profile (GOEP), Object Push Profile (OPP), File Transfer Profile (FTP), Headset Profile, Personal Area Network Profile (PAN)	Windows 98, ME, 2000, XP	2.84x1.17x.33"		2 years	128-bit encryption, two-color LED status indicator, 723 Kbps, range 330 feet	
PC Card	4312	\$44.95	Adapter	PC Card Type II, PCMCIA	Bluetooth v1.1, General Access Profile (GAP), Service Discovery Application Profile (SDAP), Serial Port Profile (SPP), Dial-up Networking Profile (DUN), Fax Profile, Local Area Network Access Profile (LAP), Generic Object Exchange Profile (GOEP), Object Push Profile (OPP), File Transfer Profile (FTP), Headset Profile, Personal Area Network Profile (PAN)	Windows 98, ME, 2000, XP			2 years	128-bit encryption, two-color LED status indicator, 723 Kbps, range 330 feet	